

Type Q3T 100 L2

General data	
Frame size	100
Housing material	Casting iron
Install model	According to the standard
Type of feet	Removable feet (Standard) <i>Fixed feet</i> (Optional)
Net weight	35.5 kg
Insulation class	F (Standard) H (Optional)
Protection degree	IP 55 (Standard) IP 56 (Optional)
Thermal protection	Without (Standard) <i>Customizable</i> (Optional)
Rotation direction	Clockwise (Standard) <i>Counter clockwise</i> (Optional)
Service duty	S1
Vibration level	A
Balance	Half-key balanced
Cable glands	1 - M20× 1.5
Cooling	IC 411
Painting color	RAL 7024 (Standard) <i>Customizable</i> (Optional)
Regulations	IEC / DIN / ISO / VDE / EN
Standard	IEC 60034

Environmental conditions	
Ambient temperature	From -20°C to +40°C
Maximum altitude	1000 m above sea level

Electrical data		
Output	3	kW
Frequency	50	Hz
Voltage (±5%)	400 690 480 828	V Δ @ 50Hz V Y @ 50Hz V Δ @ 60Hz V Y @ 60Hz
Rotation speed	2900 3480	RPM @ 50Hz RPM @ 60Hz
Rated current	5.65	A (In) @ Δ 50Hz
Starting current	9.5	×In
Rated torque	9.88	Nm (Mn)
Starting torque	2.5	×Mn
Breakdown torque	2.8	×Mn
Efficiency	87.1 88.5 86.8	IE3 @ 100% load @ 75% load @ 50% load
Power factor cosφ	0.88	@ 100% load

Mechanical data		
Bearings brand	C&U <i>Customizable</i>	(Standard) (Optional)
Bearings type	6206 2RS C3 6206 2RS C3	(DE) (NDE)
Lifetime of bearings		32000 hours
Allowed radial load Allowed axial load		882 N 7667 N
Grease type		-
Lubrication interval of NDE bearing Lubrication interval of DE bearing		- h - h
Moment of inertia	0.004960	Kg*m ²
Noise level	76	dB(A)